

## TECHNICAL DATA : SMV 33 G3

<b>LIFTING DATA</b>		
Lift capacity / Min Load center (up to max lift height)	kg / mm	30000 / 1490
Lift capacity / Max Load center (up to max lift height)	kg / mm	28000 / 1730
Stacking height (of 9'6" / 8'6" containers)		3 / 3
Lifting speed, unloaded / at rated load	m/s	0,32 / 0,27
Lowering speed, unloaded / at rated load	m/s	0,40 / 0,40
<b>DRIVING DATA</b>		
Drive speed forward, unloaded / at rated load	km/h	22 / 20
Drive speed reverse, unloaded / at rated load	km/h	22 / 20
Incline (driving ability) at rated load at 0 km/h/at 2 km/h	%	42 / 30
Towing (power ability) at rated load at 0 km/h/at 2 km/h	kN	315 / 215
<b>SERVICE WEIGHT / AXLE PRESSURE</b>		
Service weight	kg	51300
Axle pressure front at LC1, unloaded / at rated load	kg	31100 / 75900
Axle pressure rear at LC2, unloaded / at rated load	kg	20200 / 5400
<b>ENGINE (electronic controlled)</b>		
Engine make / model name		Scania DI-12-54A1
Emission approval EU / US		EU Stage II / US Tier 2
Monitoring / emission controlled / CanBus		Yes / yes / yes
Fuel/type of engine/intercooler		Diesel / 4-stroke / yes
Power ISO 3046 / at speed	kW / rpm	222 / 2100
Torque ISO 3046 / at speed	Nm / rpm	1446 / 1200
Displacement / No. of cylinders / Type	L / /	11,7 / 6-cylinder / Inline
Fuel consumption, normal drive	L/h	12 - 14
Alternator, type/power / capacity	/ W / Amp	AC / 1820 / 65
Starting battery, voltage/capacity	V / Ah	2 x 12 / 140
<b>TRANSMISSION (electronic controlled)</b>		
Transmission make / model name		Dana TE-27400
Monitoring / reverse protection / CanBus		Yes / yes / yes
Clutch, type		Torque converter
Transmission type / type of shift gear		Softshift - Powershift / Automatic
No. of gears, forward/reverse		4 / 4
<b>DRIVE AXLE &amp; BRAKE SYSTEM</b>		
Drive axle make / model name		Kessler D91
Drive axle type / drive axle width	/ mm	Differential + hub reduction / 3440
Driving brake system, type / affected wheels		Oil cooled Wet Disc Brakes / drive wheels
Parking brake system, type / affected wheels		Dry disc brake / spring release / drive wheels
<b>STEER AXLE &amp; STEER SYSTEM</b>		
Steer axle type / steering system		Double acting cylinder / hydraulic servo assisted
<b>WHEELS</b>		
Number of wheels, front + rear / type (*driven)		4*+2 / pneumatic
Tire pressure front / rear	MPa	0,9 / 0,9
Tire dimensions (Ply rating) front / rear	Inch (No)	16.00 x 25" (PR 32) / 16.00 x 25" (PR 32)
Rim dimension front / rear	Inch	11.25 x 25" / 11.25 x 25"
<b>HYDRAULIC SYSTEM</b>		
Hydraulic pump make / model name		Parker & Hannifin / P2-series
Hydraulic system / pump type		Load sensing system / variable piston pump
Power-on-demand / Low energy		Yes / yes
Hydraulic oil pressure mast / spreader	MPa / MPa	22 / 15
<b>TANK VOLUMES</b>		
Diesel tank volume	L	371
Hydraulic tank volume	L	406
<b>LIFT EQUIPMENT &amp; SPREADER</b>		
Lift mast model / mast type / design		Duplex standard / 2-stage / free visibility
Spreader make / model name		ELME 818
Spreader type / capacity		Toplift telescopic / 20-40 ft containers
Spreader locking type / No. of containers		4 x top twist locks / 1
Sideshift stroke / liftingeyes	mm	± 200 / 4 x in the corners
Spreader slew turn / spreader reach stroke	Deg / mm	± 3 / 0 - 240 (each side)
Pile Slope type / pile slope stroke (side tilt)	/ Deg	Mechanical MPS / (± 4,8)
<b>OTHERS</b>		
Noise level (inside Cab / Lm)	DIN 45635	dB(A) 73
Noise level (inside Cab/ LpAZ)	EN 12053	dB(A) 75
Noise level (outside at 7 m/ Lwa)	2000/14/EC	dB(A) 111
<b>NORMS &amp; STANDARDS</b>		
Machine Directive in Europe	98 / 37 EC	Yes
Stability of Industrial Trucks	ISO 1074	Yes
Safety of Industrial trucks	EN 1551	Yes

